

HPL


High-performance lamps

Product benefits

- Optimum use of the generated light in the spotlight



Product family datasheet



Product line drawing

Product line drawing

Product family datasheet

Technical data

Product description	Electrical data	Photometric data	Dimensions & weight				Lifespan	Additional product data	Capabilities
	Nominal voltage	Color temperature	Diameter	Length with base excl. base pins/connection	Light center length (LCL)	Illuminated field	Lifespan	Base (standard designation)	Burning position
HPL 93728 575 W 230 V	230 V	3200 K	19.0 mm	98.00 mm	60.3 mm	9.5*11.5 mm ^{2 1)}	400 h	2 pins	Any
HPL 93728 575 W 240 V	240 V	3200 K	19.0 mm	98.00 mm	60.3 mm	9.5*11.5 mm ^{2 1)}	400 h	2 pins	Any
HPL 93728 LL 575 W 230 V	230 V	3050 K	19.0 mm	98.00 mm	60.3 mm	14.5*11.0 mm ^{2 1)}	1500 h	2 pins	Any
HPL 93728 LL 575 W 240 V	240 V	3050 K	19.0 mm	98.00 mm	60.3 mm	14.0*14.0 mm ^{2 1)}	1500 h	2 pins	Any
HPL 93729 750 W 230 V	230 V	3200 K	19.0 mm	104.00 mm	60.3 mm	7.5*11.5 mm ^{2 1)}	300 h	2 pins	Any
HPL 93729 750 W 240 V	240 V	3200 K	19.0 mm	104.00 mm	60.3 mm	7.5*11.5 mm ^{2 1)}	300 h	2 pins	Any
HPL 93729 LL 750 W 230 V	230 V	3050 K	19.0 mm	104.00 mm	60.3 mm	15.5*11.0 mm ^{2 1)}	1500 h	2 pins	Any
HPL 93729 LL 750 W 240 V	240 V	3050 K	19.0 mm	104.00 mm	60.3 mm	15.5*11.0 mm ^{2 1)}	1500 h	2 pins	Any

Product description	Certificates & standards	Country specific categorizations
	EEL – Energy Label	Order reference
HPL 93728 575 W 230 V	B	93728 575W 230V
HPL 93728 575 W 240 V	C	93728 575W 240V
HPL 93728 LL 575 W 230 V	B	93728 LL 575W 2
HPL 93728 LL 575 W 240 V	C	93728 LL 575W 2
HPL 93729 750 W 230 V	B	93729 750W 230V
HPL 93729 750 W 240 V	B	93729 750W 240V
HPL 93729 LL 750 W 230 V	C	93729 LL 750W 2
HPL 93729 LL 750 W 240 V	C	93729 LL 750W 2

Product family datasheet

¹⁾ Type of filament 6-C8

Product family datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (cover panel etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. Because of the heat produced only heat-resistant lamp connections (holders) may be used. Do not operate near people, or any materials that are flammable, sensitive to heat or affected by drying out. Detailed information is available on request.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.