



Single Ended Halogen T25 230-240V 88470

Product information

Quartzline® lamps designed for optimum performance in today's precision range of stage, studio and architectural luminaires. Full range up to 24,000 W -Range of bases to meet the needs of OEMs -Chromised seal protection up to 500° C.


Application areas



() Theatre













Product data

| Product Code | 88470 |
|-----------------------------|-----------------------|
| Bulb Shape | Tubular |
| Bulb Diameter [mm] | 23 |
| Maximum Overall Length [mm] | 89 |
| Net weight per piece [g] | 24 |
| Gross weight per piece [g] | 35 |
| Brand | General Electric (GE) |
| Cap/Base | GY9.5 |

Performance data

| Weighted energy consumption [kWh/1000h] | 498.33 |
|--|--------|
| Energy efficiency class (EEC) | С |
| Rated Life [h] | 360 |
| Nominal correlated colour temperature (CCT) [K]] | 3000 |
| Nominal lumens [lm] | 11000 |
| Colour Rendering Index (CRI) [Ra] | 100 |

Electrical data

| Coil type | C-13D |
|--------------------------|-------|
| Dimming Capability | Yes |
| Ballast Required | No |
| Nominal power [W] | 500 |
| Nominal lamp voltage [V] | 240 |





Logistic data

| ode 0 | 0043168884709 |
|---------------------|----------------------|
| Quantity 2 | 24 |
| quantity 5 | 504 EUR, 600 UK |
| quantity EUR 5 | 504 |
| quantity UK 6 | 500 |
| quantity EUR (PC) 4 | 4032 |
| quantity UK (PC) 4 | 4800 |
| case size 1 | 170 x 255 x 130 (mm) |
| ct status A | Available |

Downloads & Links Go to the catalog site (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) High-res images / Technical drawings (HTTP) Certificate for the Quality Management System of GE Lighting EMEA (PDF) Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination